



514.335.8413
1.855.858.0644

info@backfloshop.com

BACKFLOW PREVENTION ASSEMBLY TEST KIT

Mid-West® Instrument

MODEL 845-5-NP

The 845-5-NP is in the list of Acceptable gauges from Both FCCC & HR-USC and CA-NV AWWA

Functions and Applications:

Identical to our popular Model 845-5 except Dial, Hoses and Carrying Case are easily identified for **NON-POTABLE** Service.

ΔP Range: 0-15 PSID / 0-100 KPA

Product Features/Benefits

- Easily identify Gauges & Hoses for NON-POTABLE Service
- Five (5) Valve Test Kit
- Specially designed for testing backflow prevention assemblies
- Soft-Seated Brass Needle Valves (with replaceable valve seats)
- Test kit is protected with 90 micron filters to minimize plugging with scale, sand, etc. The filter elements can be cleaned or replaced
- Portable/Removable from a durable molded plastic carrying case
- Improved case with storage compartments for Fittings & Tools
- Test procedures are laminated in clear plastic
- 1 year Warranty

Specifications

- Gauge: Diaphragm Type Differential Pressure
- Dial size & range: (4 ½"), 0-15 PSID / 0-100 KPA
- Differential pressure accuracy ± 0,2 P.S.I.D. (descending)
- Working pressure: 200 PSIG
- Body material: glass reinforced engineering thermoplastic
- Wetted internals: EP Elastomers, brass and 316 S.S. metal parts
- Line pressure gauge: 1 ½" diameter / Range: 0-200 PSIG
- Hoses with inline filters & schrader ¼" brass coupler end fittings
- Hose length: three (3) hoses, each of 5 ft long (color-coded)
- Bleed tube: one (1) each of 4 ft long clear bleed tube
- Adaptor fittings: three (3) sets of brass fittings provided for hookup to all standard size test cocks
- Gauge weight: 3.6 lbs / 1.6 kg (estimated shipping weight: 11.5 lbs / 5 kg)
- Size: 18 ½" L x 9" W x 9 ¾" H
- Temperature limitations: maximum 150°F/65°C (**FREEZING TEMPERATURES MUST BE AVOIDED**)



backfloshop.com

G-9995 rue de Châteauneuf, Brossard (Québec) J4Z 3V7